


CHCNAV

AA15

PREMIUM AIRBORNE
LiDAR SOLUTION



MAPPING
& GEOSPATIAL

EFFICIENT AND POWERFUL CORRIDOR MAPPING SENSOR

The AlphaAir 15 (AA15) is a lightweight airborne LiDAR system developed by CHCNAV. It combines long-range scanning capability and high accuracy with an extremely fast data acquisition rate, all in a compact design. The AA15 is ideal for scenarios where high density data is required to accurately extract building and road information from point clouds. For large-scale operations, especially in mountainous areas with significant elevation changes, the AA15 accurately detects ground features even at the bottom of valleys. Equipped with a variety of cameras to meet diverse needs, the system can be mounted on light aircraft, helicopters or UAV platforms.

HIGHEST DATA QUALITY

Utilizing CHCNAV's patented tilted-prism technology, the AA15 delivers 15 mm linear accuracy on long-range scans up to 150 meters. This innovative technology supports echo digitization and online waveform processing. With a continuously rotating polygon mirror, the AA15 achieves scan speeds of up to 600 lines per second, combined with 2 million pulses per second, resulting in high-density point clouds that recreate the world with remarkable precision.

STRONG VEGETATION PENETRATION

The AA15 excels in vegetation penetration thanks to its advanced multi-target capability that supports up to 16 returns per laser pulse and 7 multi-period zone processing. With a high point frequency of 2 million pulses per second, the AA15 increases the probability of laser penetration through vegetation, making it easier to obtain more ground points.

PRODUCTIVE SURVEY

Capturing 2 million points per second and with a maximum range of 1800 meters, the AA15 can be mounted on a variety of platforms. With a flying height of up to 700 meters, it provides minimal point loss over large areas, making it ideal for high point density corridor mapping applications such as power lines, highways, railroads and pipeline inspections. It is also well suited for urban mapping projects.

IMAGING QUALITY

For high-resolution imaging needs, the AA15 supports several external camera accessories, including CHCNAV's 45 or 61 MP full-frame calibrated cameras and a 130 MP half-frame oblique camera. Users can also integrate cameras from third-party oblique or ortho-camera manufacturers. The combination of high-density point clouds and high-resolution imagery facilitates rapid mesh model construction and provides detailed texture information.

AIRBORNE PLATFORM COMPATIBILITY

Featuring CHCNAV's unified Alphaport interface, the AA15 allows quick and easy connection to power sources and cameras with a single click. Its compact design and light weight of only 2.5 kg ensures seamless integration into various UAS, UAV, RPAS, small manned aircraft and helicopters.

COMPLETE ECOSYSTEM

CHCNAV offers a comprehensive package for integrating LiDAR solutions into your geospatial services. The SmartGo App enables fully automated reality capture and real-time mission monitoring, while the CoPre and CoProcess software suite streamlines post-processing and feature extraction, providing an efficient and user-friendly data workflow.



PREMIUM AIRBORNE DATA



Lightest in Class

The AA15 weighs only 2.5 kg, making it the lightest LiDAR in its class and allowing it to be mounted on DJI drones.



Various Cameras

Using various camera options, the AA15 can produce multiple results in a single flight, including RGB point clouds, DOM, DEM and 3D models.



Data Fusion

The AA15's dense point cloud helps to quickly build mesh models, and with image mapping texture, it can achieve efficient reconstruction of realistic 3D models in CoPre.




Automatic Extraction

Using CHCNAV CoProcess software, users can automatically detect railroads, roads, and buildings based on high-density AA15 data.

SPECIFICATIONS

General system performance				Imaging system						
Absolute Hz accuracy	2 cm ~ 5 cm RMS ⁽¹⁾			Resolution	45 MP					
Absolute V accuracy	2 cm ~ 5 cm RMS ⁽¹⁾			Focal length	21 mm/35 mm					
Mounting	Quickly install & release design, easily switch between various UAV platforms, RPAS, small manned aircraft and helicopters			Sensor size	36 mm x 24 mm (8184 x 5460)					
				Pixel size	4.4 μm					
Weight of instrument	2.5 kg			Min photoing interval	1 s					
Dimensions of instrument	247 mm × 126 mm × 156 mm			FOV	81.2*59.5 / 53.4*37.8					
Data storage	512 G (Optional for 1 T)			Environmental						
Coping speed	80 Mb/s			Operating temperature	-20°C to +50°C					
Imaging system	External camera C5/C30 (Optional for third-party oblique or orthho cameras)			Storage temperature	-20°C to +60°C					
				IP rating	IP64					
				Humidity (operating)	80%, non-condensing					
Positioning and orientation system				Electrical						
GNSS system	Multiple GPS, GLONASS, Galileo BeiDou, SBAS and QZSS constellation, L-Band			Input voltage	DC 24 V (15 ~ 27 V)					
IMU update rate	600 Hz			Power consumption	60 W					
Attitude accuracy after post-processing	0.005° RMS pitch/roll 0.010° RMS heading			Equipped software						
Position accuracy after post-processing	0.010 m RMS horizontal 0.020 m RMS vertical			CoPre intelligent processing Software	Data copy, POS process, Adjust & Refine, Generate point cloud					
				CoPre intelligent processing Software	Terrain module, Road module, Volume module					
Laser scanner										
Laser product classification				Class 3R Laser Product according to IEC 60825-1:2014						
Laser pulse repetition rate PRR	100 kHz	200 kHz	300 kHz	400 kHz	500 kHz	800 kHz	1M Hz	1.5M Hz	2M Hz	
Max. range, @p >20% ⁽²⁾	900 m	720 m	700 m	610 m	545 m	430 m	385 m	315 m	272 m	
Max. range, @p >80% ⁽²⁾	1800 m	1440 m	1400 m	1220 m	1090 m	860 m	770 m	630 m	500 m	
Max.Operating Flight Altitude AGL, @p >20% ⁽³⁾	700 m	570 m	550 m	480 m	430 m	340 m	300 m	250 m	200 m	
Laser divergence angle					0.032°					
Minimum range					5 m					
Accuracy ⁽⁴⁾					15 mm (1σ,@ 150 m)					
Precision ⁽⁵⁾					5 mm (1σ,@ 150 m)					
Multi-Period capability					Up to 7 zones					
Field of view					75°					
Scanning mechanism					Rotating mirror					
Max. measurement rate					2,000,000 meas./sec.					
Scan speed (selectable)					50 ~ 600 scans/sec					

*Specifications are subject to change without notice.
(1) According to CHCNAV test condition :150 m AGL with 8 m/s speed. (2) Typical values for average conditions. (3) Flat terrain assumed. (4) Accuracy is the degree of conformity of a measured quantity to its actual (true) value. (5) Precision is the degree to which further measurements show the same results.



© 2024 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHCNAV and CHCNAV logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision June 2024.